

## HKS lounge 9 mm, oak

<b>Type/Construction</b>	Wooden flooring planks for glueless installation, toplayer approx. 0,6 mm oak, high quality birch plywood base. Integrated cork underlay underneath, approx. 1,5 mm.
<b>Dimensions</b>	9 x 178 x 1.500 mm
<b>Packaging</b>	white boxes, 15 pcs. per box = 4,005 m <sup>2</sup> ; 1 pallet = 24 boxes = 96,12 m <sup>2</sup>
<b>Profile</b>	Välänge 5G click system (fold-down), micro-bevel all around (G04)
<b>Surface</b>	matt lacquered in 5 different colours: Mojito, Gin Tonic, White Lady, Daiquiri, Cuba Libre
<b>Production</b>	according to EN 14354
<b>Grading</b>	Prime grade
<b>Installation</b>	floating, without glue (according to the installation guide)
<b>Maintenance</b>	regularly dry cleaning by using a soft cloth or vacuum cleaner, also with a soft parquet brush; occasional cleaning with warm water, by using a wring out cloth, if needed suitable parquet soap can be added
<b>Underfloor Heating</b>	only warm water heating-system, no electric heating-system, max. surface temperature 27°C heat conductivity, thermal resistance 0,068 m <sup>2</sup> K/W with equal heating
<b>Fire resistance</b>	C <sub>fl</sub> -s1
<b>Labelling</b>	CE
<b>Hints</b>	Wooden floorings are a natural product, due to climate conditions joints can occur in winter months and swell can occur in the summer months. Therefore an expansion gap of minimum 10 mm to the walls is necessary. According to the behaviour of the planks the customer must be advised about the floating installed floor.



The material must be checked before installation, claims after the installation are impossible.